

Technical Datasheet

Q 20-030 Multiflex Putty

Characteristics:

Highly elastic multifunctional putty designed especially for application on plastic substrates including polypropylene. Easy application and modelling. It can be used as fill and as fine putty. Provides pore-free, easy to sand coating. Adheres also to metal substrates, including steel, galvanized steel and aluminium, as well as to polyester surfaces.

Application:

The surface must be clean, dry, degreased and matted with abrasives. Thoroughly mix putty by weight with 2-3% of BPO hardener. Apply within 3 - 5 minutes at 20°C. Higher temperature can reduce the pot life and accelerates the drying time.

Note:

Using too much hardener can lead to topcoat discoloration. It is not recommended to use putty below 15°C. Do not apply over wash primers and one component acrylic products.

Technical data:

Density: 2,0 – 2,1 g/cm³


Colour: dark grey




2004/42/II(b)(250)<250




Cleaning
60-010



BPO- 2-3%



Pot life
3 -5 min 20°C




20 - 30 min 20°C




Hand sanding / dry:
P150 - P320



Machine sanding / dry:
P150 - P320



Shelf life:
12 Month



Store in cool place



Latex / Nitril

This data sheet is for information purpose only. To our knowledge the data provided complies with the latest standard and is based on years of experience in the manufacturing of our products.

Copyright: Q-Company 2017, all rights reserved.

Q-Company Int. GmbH / Beckershof 3 / D-24558 Henstedt-Ulzburg / Germany

Version: 02.01.2017