



REFINISH


# Q 50-120

# UBC Wax

## Characteristics

50-120 is a wax coating for the repair and reinforcement of existing underbody coatings based on PVC, rubber, bitumen or wax. The product protects against corrosion and provides excellent protection against moisture, brine and road salt.

## Physical Characteristics



12 month



2004/42/IIB(e)(840)<840

## Application



cleaning



5 - 10 mm  
4 - 6 bar



1 - 2



300 - 500 μm

Consumption: 2 m<sup>2</sup>/l

## Processing tips



Because of its thixotropy, 50-120 UBC Wax can be applied in thick layers on e.g. mudguards without dripping. Do not spray on engine, exhaust pipes and the entire brake system. Mask them prior to application!

## Storage



Store the product in a ventilated place. Keep away from direct exposure to sunlight. Keep between +15°C and 25°C.

## Safety



For more informations check the safety data sheet.



This data sheet is for information purpose only. To our knowledge the data provided complies with the latest standard and is based on years of experience in the manufacturing of our products. Copyright: Q-Company Int. GmbH, all rights reserved.

Version: 25-05-2023

Q-Company Int. GmbH • Lentföhrdener Strasse 12-14 • D-24576 Weddelbrook, Germany  
+49 (0)4192 891 420 • [www.qrefinish.com](http://www.qrefinish.com) • [info@qrefinish.com](mailto:info@qrefinish.com)